

5880 GALLON (140 BARREL) SINGLE COMPARTMENT ULTRA LIGHT LOW PRO STEEL VACUUM TANDEM SEMI TRAILER



GENERAL CONSTRUCTION

MODEL: STLP-140-S

SPECIFICATIONS: NON-CODE, NON-SPEC

PRODUCT: WATER AND VARIOUS WASTE PRODUCTS

MAWP: 23 IN HG/25 PSIG

CAPACITY: 5880 (140 BBL) GALLONS SHELL FULL

5880 GALLON (140 BARREL) SINGLE COMPARTMENT ULTRA LIGHT LOW PRO STEEL VACUUM TANDEM SEMI TRAILER - CONTINUED

COMPARTMENTS: SINGLE

DESIGN: FRAMELESS LOW PROFILE BARREL

SHELL LENGTH: 480" (40' 0")

OVERALL LENGTH: 516" (43'-0") PEAK OF FRONT HEAD TO REAR BUMPER

SHELL: .250" A36 STEEL

HEAD/BAFFLE: .250" A36 STEEL

(2) .250 BAFFLES; (1) REAR OF FRONT SUBFRAME AND

(1) FRONT OF REAR SUBFRAME

RINGS: (8) STEEL STIFFINER RINGS

BUMPER: 87" WIDE STEEL DOT

OVERTURN

PROTECTION: WIDEST CENTER OF GRAVITY, LOW PROFILE WITH 102" WIDE

AXLES

DOME COVER: (4) 20" NAT VAC WING NUT STYLE; ONE TOP FRONT OF VESSELL

BETWEEN FRONT HEAD AND FRONT BAFFLE; ONE CENTER OF VESSEL BETWEEN THE BAFFLES; ONE TOP REAR OF VESSEL BETWEEN REAR HEAD AND REAR BAFFLE; MANWAY CENTER OF

REAR HEAD.

VENT: (1) 1 ½" BRASS PRESSURE RELIEF VENT:

(1) 1 ½" BRASS VACUUM RELIEF VENT;

KING PIN: 48" GROUND TO KINGPIN PLATE; 18" KINGPIN SETTING

VACUUM EQUIPMENT

PRIMARY SHUTOFF: 12" NVE STEEL;

3" HOSE BARB OUTLET; PVC BALL CAGE AND STAINLESS STEEL FLOAT BALL; LOCATE AT TOP FRONT OF VESSEL BETWEEN

FRONT HEAD AND FRONT BAFFLE

SECONDARY SHUTOFF: NVE STEEL 10 GALLON; F-901-8B- -SS

3" HOSE BARB INLET/3" NPT OUTLET; PVC BALL CAGE AND

STAINLESS STEEL FLOAT BALL

SIGHT GLASS: NONE

5880 GALLON (140 BARREL) SINGLE COMPARTMENT ULTRA LIGHT LOW PRO STEEL VACUUM TANDEM SEMI TRAILER - CONTINUED

PRESSURE GAUGE: 2 ½" GLYCERIN FILLED PRESSURE/VACUUM GAUGE ON 2"

BLOWDOWN LINE AT REAR

PUMP: NONE

AIR HOSE: 3" PRESSURE/VACUUM HOSE CONNECTING PRIMARY AND

SECONDARY

GASKETS: BUNA MANHOLE AND VALVE GASKETS

LOAD/DISCHARGE FITTINGS

LOAD AND DISCHARGE: (2) 4" THREADED FLANGE WITH 4" BUTTERFLY VALVES ON REAR

SUMP BOX WITH REDUCER TO 3" WITH BLOWDOWN LINES WITH

DRIP PAN

BODY TRIM

LADDER: AT STREETSIDE REAR

CATWALK: FULL LENGTH

FENDERS: (2) RIBBED ALUMINUM FULL TANDEM SINGLE RADIUS FRONT

(2) RIBBED ALUMINUM FULL TANDEM DOUBLE RADIUS REAR

(2) MUDFLAPS AT REAR AND HALF AT FRONT

HOSE TRAYS: HALF LENGTH ALUMINUM HOSE TRAYS

HOSE HOOKS: NONE

CABINET: (1) STEEL PLATE 18" X 18" X 36" STREET SIDE IN FRONT OF

TANDEMS

PUMP PLATFORM: NONE

PLACARDS: NONE

LIFTING LOOPS: NONE

ELECTRICAL SYSTEM

LIGHTS: TAIL AND MARKER LIGHTS

3-TAIL LIGHT GROUP EACH SIDE AT REAR. OUTSIDE -

RED CLEARANCE/TURN, CENTER - AMBER TURN, INSIDE - RED

STOP/TAIL

(3) MARKER SINGLE FUNCTION LIGHTS PER SIDE

5880 GALLON (140 BARREL) SINGLE COMPARTMENT ULTRA LIGHT LOW PRO STEEL VACUUM TANDEM SEMI TRAILER - CONTINUED

(1) SEQUENTIAL TURN SIGNAL EACH SIDE NEAR CENTER

MOUNTED OFF FRONT OF HOSE TUBES

I.D. CLUSTER ON REAR HEAD

LICENSE LIGHT AND BRACKET ON REAR HEAD

WORKLIGHTS: (2) REAR MOUNTED ON REAR HEAD TO LIGHT DISCHARGE AREA

UNDERCARRIAGE

SUSPENSION: (2) WATSON & CHALIN 25K AIR SPRING

AXLES: (2) 5" ROUND, 71 ½" TRACK, 5/8" WALL

BRAKES: 16 1/2" X 7" "Q" LININGS

WHEEL END TYPE: 10 STUD HUB PILOT (HP10)

HUBS: (4) STEMCO OIL SEALS AND HUBCAPS

DRUMS: (4) OUTBOARD

DUST SHIELDS: NONE

ABS/BRAKE SYSTEM: MERITOR/WABCO (4S/2M) PLC ABS

BRAKE CHAMBERS: (4) 30/30 SPRING BRAKE CHAMBERS

SLACK ADJUSTERS: (4) 5 1/2" AUTOMATIC SLACK ADJUSTERS

WHEELS: (8) 8.25 X 22.5 STEEL

TIRES: (8) 255/70R22.5 ROADONE CHIP RESISTANT

FRONT COUPLER: INVERTED STEEL KINGPIN PLATE ASSEMBLY

LANDING GEAR: TWO SPEED

STREETSIDE CRANK AND SAND SHOES

BOLSTER STYLE BRACKET

TIRE CARRIER: NONE

BUMPERS: STEEL D.O.T. BUMPER

FINISH

5880 GALLON (140 BARREL) SINGLE COMPARTMENT ULTRA LIGHT LOW PRO STEEL VACUUM TANDEM SEMI TRAILER - CONTINUED

PAINT: STEEL PARTS PRIMED AND ACRYLIC ENAMEL

LINER: SHERGLASS

CONSPICUITY: 2" WIDE RELFECTIVE TAPE

D.O.T. MINIMUM COVERAGE

SIGNS: STANDARD SOUTHERN EMBLEM

CALIBRATION: THEORETICAL IN 1" INCREMENTS

REGISTRATION: NONE